

FIJAMOR

Paint Sealant

DESCRIPTION

Indicated to improve the adhesion of paints, specially on gypsum, perlite or old substrates.

TECHNICAL CHARACTERISTICS

Product based on an emulsion of very short chain acrylic co-polymers.

ADVANTAGES AND USES

- Great penetration on the substrate.
- Excellent adherence which favours the application of paint.
- Good homogeneization of substrate.
- Excellent cohesion properties on substrates not very estable or not very solid.

SUITABLE SUBSTRATES

NEW SUFARCES

- Eliminates dust, grease and other contaminants
- Apply FIJAMOR according to instruction for use.

OLD SURFACES

- Eliminate mould stains with a household acid. Also eliminate any paints or remainings of other construction materials.
- Level the surface with a suitable product. Let dry and sand.
- Apply FIJAMOR according to instruction for use.

APPLICATION PROCEDURE

- Shake until product is homogeneous.
- Dilute with 2 or 3 parts of water.
- Apply with a brush, roller or a pressure air gun.
- Touch dry: 60 min.
- Clean tools with water immediately after use.

RECOMMENDATIONS

- Do not apply below 5°C nor above 30°C., under direct sunlight, rain or risk of frost.
- Store in fresh and dry places.

PACKAGING AND STORAGE

5 and 25 l bags.
Shelf live: 1 year in sealed original packaging.

TECHNICAL DATA

(Statistical data obtained under standard conditions)

Solvent	Water
Specific weight	1,03 Kg/L

ADDITIVES AND PRIMERS

FIJAMOR

LEGAL DISCLAIMER

Efficiency	6-8 m ² /L according supports
Dry to touch	60 minutes
Time between hands	8 hours minimum

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.