

MORCEMCRIL® FONDO



DESCRIPTION

High quality acrylic primer indicated as a coloured wash for MORCEMCRIL. It improves adherence, eases application, homogenises substrate suction, and gives a base coloured covering. Improves covering and adherence of finishing acrylic mortar, while keeping high water vapour permeability. Easy to apply and excellent adherence to substrate.

TECHNICAL CHARACTERISTICS

Product based on acrylic resin, mineral pigments and organic and inorganic additives.

ADVANTAGES AND USES

- Good covering.
- Water proof against rain.
- Water vapour permeable.
- Good resistance to substrate alkalinity.
- Good product homogenisation and easy application.

SUITABLE SUBSTRATES

- Substrates must be sound, clean, dry, free from dust, grease, without cracks and loose parts.
- On low cohesion or very porous substrates, treat before with a layer of FIJAMOR diluted with 2 or 3 parts of water.

APPLICATION PROCEDURE

- Stir the material until perfect homogenisation.
- Can be diluted with 5% with water to match the work conditions and substrate to be primed.
- Typically a single layer of the product is enough.

APPLICATION TOOLS

- Application can be done by brush, roller or spray, after adequate dilution.
- Protect surrounding areas thoroughly.
- Clean tools with water immediately after use.

RECOMMENDATIONS

- Do not apply at temperatures below 5°C or above 30°C, under direct sunlight, rain or risk of frost.
- Do not apply with relative humidity greater than 85% or on wet supports.
- Store in fresh and dry places.

PACKAGING AND STORAGE

FONDO MORCEMCRIL comes in plastic cans of 25 Kg.

Shelf life: 2 year in sealed original packaging, kept in temperate and dry places, away from direct sun and outdoor conditions. Temperature must be kept between 5°C and 35°C.

TECHNICAL DATA

(Statistical data obtained under standard conditions)

Binder

Acrylic Resin

DECORATIVE PLASTERS

MORCEMCRIL® FONDO

LEGAL DISCLAIMER

Solvent	Water
Finish	matt/stone-like
Viscosity (22°C)	80 dPas +/- 10
Specific weight	1,53 +/- 0,05 Kg/l
Approximate Yield	4 at 5 m²/Kg
Dry out times	1 hour to touch. Total: 2 hours

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.