



MORCEMSEC® MULTIPURPOSE

MORCEMSEC®

MULTIUSOS

Dry plastering mortar



DESCRIPTION

Dry mortar for plastering and masonry jobs in general.

TECHNICAL CHARACTERISTICS

Product based on high resistance cement, selected aggregates, and other additives

ADVANTAGES AND USES

- To be applied directly on brickworks.
- Masonry works.
- Plaster and stucco works.
- Terrazzo floorings.

SUITABLE SUBSTRATES

- Conventional cement and brickwork based substrates.
- Substrates must be resistant, stable, sound and clean, free of dust, demolding agents, organic products, etc.
- In case of hot or windy weather conditions or when applying over absorbent substrates, it is advisable to wet the substrate and wait till the thin layer of water disappears.
- Do not apply on gypsum or on paint.

APPLICATION PROCEDURE

- Add water and mix by hand or mechanically until it takes on an even and workable consistency.
- For plaster works, spread the mortar on the substrate with a trowel and let rest enough time before floating.

RECOMMENDATIONS

- Do not apply below 5°C nor above 30°C.
- Do not apply when there is a risk of frost, rain, strong wind or direct sunlight.
- For a thickness of over 1,5 cm, it is advisable to apply the product in two coats.
- In extreme weather conditions (strong winds or high temperatures) it is necessary to water the product with light sprinklers the day after applying it.

PACKAGING AND STORAGE

25 kg plastic-lined paper bags.

Shelf life: 1 year in sealed original packaging, sheltered from weather conditions and humidity.

TECHNICAL DATA

(Statistical data obtained under standard conditions)

Aspect

WHITE or GREY powder

PRE-MIX PLASTERS AND MORTARS

MORCEMSEC® MULTIPURPOSE

LEGAL DISCLAIMER

Adhesion	$\geq 0,2 \text{ N/mm}^2$
UNE-EN 998-1 Classification	GP CSIV W0
Approximate yield	Depending on use

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.