



MORCEM® ESTUCO EXTRA FINO

MORCEM® STUCCO EXTRA THIN

Colored rendering and finishing mortar



DESCRIPTION

Lime mortar for wall covering and decorating.
Outdoor and indoor.

TECHNICAL CHARACTERISTICS

Aerial lime based product, with balanced grain size distribution aggregates and other additives.

ADVANTAGES AND USES

- High adherence.
- To be applied indoors and outdoors.
- No paints necessary. Excellent façade finishes.
- Environmentally friendly, this product is included in the "Green Line".

SUITABLE SUBSTRATES

Should always be applied over a smooth base of MORCEM FINE STUCCO.

APPLICATION PROCEDURE

- Add water and mix by hand or mechanically until it takes on an even and workable consistency and lump-free.
- Apply MORCEM STUCCO EXTRA FINE over a smooth base of MORCEM FINE STUCCO.
- Spread the mixed product.
- The paste is spread using a steel trowel, leaving a thickness less of 1 mm.
- Smooth out the surface with a steel trowel until a shiny texture is obtained.

RECOMMENDATIONS

- Do not apply directly on the wall (brick, concrete block, etc) given that the purpose of this material is strictly decorative and must be always applied over MORCEM STUCCO THIN.
- Do not apply below 5°C nor above 30°C.
- Do not apply when there is a risk of frost, rain, strong wind or direct sunlight.
- It is not advisable to apply on horizontal or sloped surfaces.
- The application of IMPERMOR is recommended on exteriors.

PACKAGING AND STORAGE

3 kg polyethylene plastic-coated paper bags.
Shelf life: 1 year in sealed original packaging, sheltered from weather conditions and humidity.

COLOUR RANGE

The colors that appears are orientative, can have some variation by technical limitations.

TECHNICAL DATA

DECORATIVE PLASTERS

MORCEM® ESTUCO EXTRA FINO

(Statistical data obtained under standard conditions)

Aspect	COLOURED powder
Thickness of application	1 mm.
Powder density	0,6 g/cm ³
Density of mass	1,4 g/cm ³
UNE-EN 998-1 Classification	CR W0

Efficiency	0,3 Kg/m ²
Colours	Check range

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.