



MORCEM® TEXTURE RESINA

MORCEM® TEXTURE RESIN

Protective resin for surfaces

DESCRIPTION

Product for protecting coatings based on a pure acrylic resin dispersion which can be used for finishing stamped mortars, protecting them from external agents by sealing the pores. This product, when applied on stamped mortars, improves their characteristics, giving them a uniform appearance. It increases cohesion due to its fine particle size.

ADVANTAGES AND USES

- Protection of coatings.
- Good adhesion and sealing capacity.
- It increases the resistance to impact and abrasion providing a finish with great hardness and good flexibility.
- It has a very good waterproofing capacity preventing the emergence of efflorescence.

APPLICATION PROCEDURE

- Apply immediately after the surface to be treated has hardened. Spread the product directly by using a spray, endeavoring to leave a uniform film, without an excessive accumulation of the product, and avoiding leaving layers which are too thick.
- It should usually be used pure, although the yield can be increased by diluting the product up to a maximum of 30% with Xylene, naphtha or aromatic hydrocarbons, depending on the condition of the substrate, the specific purpose of the application and the effectiveness of the finish which is wanted.

RECOMMENDATIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply if there is a risk of frost, rain, strong wind, direct sunlight or if the relative humidity is greater than 85%.
- The product is harmful and flammable under normal application conditions. It is necessary to use the special measures contained in the safety datasheet and to comply, at all times, with the stipulations of the Law on Prevention of Occupational Risks.

PACKAGING AND STORAGE

25 liter containers. Store in its sealed original packaging, sheltered from weather conditions and humidity, and avoid exposing it to temperatures below 5°C or above 35°C.

TECHNICAL DATA

(Statistical data obtained under standard conditions)

Appearance	Transparent liquid
Acrylic	Binder
Diluent	Organic solvent
Density at 20°C	0.89 ± 0.02 g/cm³
Solubility	In most aromatic hydrocarbons
Finish	Semi-gloss

DECORATIVE PLASTERS

MORCEM® TEXTURE RESINA

LEGAL DISCLAIMER

Solid content	27.5 ± 0.5 %
Category according to R.D. 227/2006	A/h (Solvent Base)
VOC Limit 2007 – 2010:	750; max: 687 g/L
Approximate yield:	7-9 m²/L

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.