



MORCEM® THERM TACO DE ANCLAJE

MORCEM® THERM ANCHOR STUD

DESCRIPTION

Anchor used to fasten insulation panels in the MORCEM® System.

TECHNICAL CHARACTERISTICS

The anchor is made of polypropylene and formed of two elements: nail and sheath.

ADVANTAGES AND USES

- Easy to apply.
- Ensures perfect fastening of the panels to the substrate.
- Resistant to oxidation.
- Range of sizes, depending on the thickness of the panel.

APPLICATION PROCEDURE

- Using a drill, make a hole in the substrate, going through the insulation panel.
- Hit the anchor with a mallet, so that it penetrates the surface of the panel and fastens the panels.

RECOMMENDATIONS

- The anchor must be at least 30 mm longer than the thickness of the insulation panel.

PACKAGING AND STORAGE

Boxes with the following format (depending on the length of the anchor):

70 mm	500 units/box
90 mm	500 units/box
110 mm	500 units/box
130 mm	250 units/box
150 mm	250 units/box

TECHNICAL DATA

(Data obtained in a laboratory under standard conditions)

Composition	Polypropylene
Weight	Approx. 0.01 kg/unit
Dimensions:	Length (mm) 70 / 90 / 110 / 130 / 150 Diameter (mm) 10

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment

by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.