

PROTECMOR

Temporary sealant



DESCRIPTION

Protects glazed or non glazed ceramic tiles from pigmented stains. Apply on the surface of the tile avoiding the joints.

TECHNICAL CHARACTERISTICS

Temporary pore sealer based on an aqueous emulsion used to protect ceramic tiles.

ADVANTAGES AND USES

- Very effective pore sealer.
- Suitable for porous tiles.
- Non permanent primer.
- Improves cleaning of joints.

APPLICATION PROCEDURE

- Shake to perfect homogeneization of the product.
- Substrate should be dry and clean of dust.
- Let dry for a few minutes.
- Spread with a clean cloth. Apply on all the surface avoiding the joints.
- Apply a second layer and allow to dry (20 min approx).
- Finally, grout with Morcemcolor.

RECOMMENDATIONS

The product must be protected from extreme temperatures, from direct sunlight and from frost.

COMSUMPTION/COVERAGE

Approximately 1 liter for each 20 sqm.

PACKAGING AND STORAGE

1 and 5 l bags.
Shelf live: 1 year in sealed original packaging.

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be,



ADDITIVES AND PRIMERS

PROTECMOR

are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.