

SPECIAL MORTARS



MORCEM® GLASS

Glass block bonding mortar



DESCRIPTION

Special adhesive to glue and grout glass blocks. High plasticity, resistance and water proofing qualities.

TECHNICAL CHARACTERISTICS

Product based on high resistance white cement, special aggregates of selected granulometry and additives which contribute to its great plasticity and easy application.

ADVANTAGES AND USES

- To be applied indoors and outdoors.
- Specially recommended to glue glass blocks.
- Waterproof and stable.
- No fissures.
- Compatible with the use of sticks.
- Its rapid setting makes application and cleaning easier.
- Great plasticity and elasticity.

APPLICATION PROCEDURE

- Add water and mix by hand or mechanically until it takes on an even and workable consistency.
- Let the mixture stand for 5 minutes and remix.
- Make sure that the glass blocks are resistant and free of dust, oil, wax, etc.
- Build the blockwork using a trowel as with ordinary brickworks. Make sure you use steel rods and plastic crosses for reinforcing
- Once the blocks have been set and grouted, clean them with a slightly wet sponge.
- Wait 24 hours to do the final cleaning using a scrubber or cloth.

RECOMMENDATIONS

- Do not apply below 5°C nor above 30°C.
- Do not apply when there is a risk of frost, rain, strong wind or direct sunlight.

PACKAGING AND STORAGE

25 kg plastic-lined paper bags.

Shelf life: 1 year in sealed original packaging, sheltered from weather conditions and humidity.



SPECIAL MORTARS

MORCEM® GLASS

TECHNICAL DATA

(Statistical data obtained under standard conditions)

Aspect	WHITE powder
Resistance to compression	> 15.0 N/mm ²
Approximate yield	12 kg/m ² for blocks of 20x20x8 cm

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.