



PUMACRIL DECORACIÓN MATE

Plastic coating for decoration

DESCRIPTION

Matt paint based on acrylic copolymers, recommended as a decorative and protective coating on all types of vertical surfaces and ceilings such as concrete, brick, plaster, cement, and all types of mineral substrates both indoors and outdoors. Excellent workability and easy application, achieving maximum coverage and whiteness.

TECHNICAL CHARACTERISTICS

Matt plastic paint based on acrylic copolymers indicated as a decorative and protective coating on both interior and exterior substrates.

ADVANTAGES AND USES

- Excellent whiteness and opacity.
- Great coverage.
- Rain waterproofing.
- Permeable to air and water vapour.
- Easy to clean.

Product with protection against contamination by fungi, mould and algae that achieves a long-lasting but not permanent preventive and retarding effect. The duration of this affectation depends on the exposure to humidity and the concentration of spores in the area, which create especially favourable conditions for the growth of micro-organisms. Therefore, a periodic preventive maintenance treatment is recommended.

SUITABLE SUBSTRATES

NEW SURFACES

- Remove dust, greases or any other possible contaminants.
- Apply a first coat of FIJAMOR diluted in 2 or 3 parts of water, to make uniform the absorption of the substrate.
- Apply the paint according to the given instructions.

OLD SURFACES

- Remove mould contamination as well as loose parts of paint or other construction materials.
- Level any possible irregularities with a suitable plaster. Let it dry and sand the area.
- Apply a first coat of FIJAMOR diluted in 2 or 3 parts of water, to set and make uniform the absorption of the substrate.
- Apply the paint according to the given instructions.

PAINTS

PUMACRIL DECORACIÓN MATE

APPLICATION PROCEDURE

- Shake until getting a perfect homogeneous mixture.
- Dilute the first coat between 10-15% in water.
- Dilute the second and subsequent coats up to 5- 10% in water.
- The cleaning of the tools will be done with water before the paint dries.

RECOMMENDATIONS

- Do not apply at temperatures below 5°C.
- Do not apply with relative humidity higher than 85% or on wet substrates.

Storage: Up to two years in its well-closed original container. Keep in cool, dry places in a sheltered place not exposed to direct sunlight, and avoiding exposure to temperatures below 5°C or above 35°C.

4 and 15 L containers

PACKAGING AND STORAGE

TECHNICAL DATA

ASPECT OF THE DRIED FILM	VALUE	ACCORDING TO SPECIFICATIONS
Colour	White	-
Finish	Matt	UNE-EN 1062-1
85° shine	6	UNE-EN ISO 2813
CHROMATIC CORDINATE L*	96,4	UNE 48073
CHROMATIC CORDINATE C*	0,4	UNE 48073
CHROMATIC CORDINATE h*	112,54	UNE 48073
BERGER WHITENESS	89-92	UNE 48073
OPACITY	95-98%	UNE-EN 13300

PHYSICAL PROPERTIES	VALUE	ACCORDING TO SPECIFICATIONS
Density	1,57 Kg/l	UNE-EN ISO 2811-1
pH	8,6	INTERNAL
Viscosidad	90 dPas (50 rpm; Husillo R6)	UNE-EN ISO 2555
Finura dispersión	20-10 microns	UNE-EN ISO 1524

REGARDING ITS FORMULATION	VALUE	ACCORDING TO SPECIFICATIONS
Non-volatile matter content	64%	UNE-EN ISO 3251
Maximum VOC content allowwed	30 g/L	2004/42/II A Classification
MAximum VOC content of the product	30 g/L	2004/42/II A Classification

PAINTS

PUMACRIL DECORACIÓN MATE

LEGAL DISCLAIMER

APPLICATION PROPERTIES	VALUE	ACCORDING TO SPECIFICATIONS
Theoretical performance	8-10 m ² /L	UNE 48282
Dry touch time	1 Hour	UNE 48301
Total dry time	2,5 Hours	UNE 48301
Thinner	Water	-
First hand solution	15 -10%	-
Second hand and subsequent dilutions	5 -10%	-
Repaint interval	3-4 Hours	-

OTHERS SPECIFIC PROPERTIES	VALUE	ACCORDING TO SPECIFICATIONS
Web rub resistance	Class 3	UNE-EN ISO 11998

Las instrucciones de forma de uso se hacen según nuestros ensayos y conocimientos y no suponen compromiso de GRUPO PUMA ni liberan al consumidor del examen y verificación de los productos para su correcta utilización. Las reclamaciones deben acompañarse del envase original para permitir la adecuada trazabilidad. GRUPO PUMA no se hace responsable, en ningún caso, de la aplicación de sus productos o soluciones constructivas por parte de la empresa aplicadora o demás sujetos intervinientes en la aplicación y/o ejecución de la obra en cuestión, limitándose la responsabilidad de GRUPO PUMA exclusivamente a los posibles daños atribuibles directa y exclusivamente a los productos suministrados, individuales o integrados en sistemas, debido a fallos en la fabricación de aquellos. En cualquier caso, el redactor del proyecto de obra, la dirección técnica o responsable de la obra, o subsidiariamente la empresa aplicadora o demás sujetos intervinientes en la aplicación y/o ejecución de la obra en cuestión, deben cerciorarse de la idoneidad de los productos atendiendo a las características de los mismos, así como las condiciones, soporte y posibles patologías de la obra en cuestión. Los valores de los productos o soluciones constructivas de GRUPO PUMA que en su caso sean determinados en la norma UNE o cualquier otra que le fuera de aplicación en cada caso se refieren exclusivamente a las condiciones expresamente estipuladas en dicha normativa y que vienen referidos, entre otros, a unas determinadas características del soporte, condiciones de humedad y temperatura, etc. sin que sean exigibles a ensayos obtenidos en condiciones diferentes, todo ello de acuerdo con lo expresamente establecido en la normativa de referencia.