



PAVILAND® RESINA A4

PAVILAND® RESIN A4

Water-based resin floor finish

DESCRIPTION

Product based on the dispersal of styrene acrylic resin with low water absorption. It has good resistance to alkalis and yellowing, as well as great flexibility and durability in the exterior. Recommended as curing liquid with an aqueous base, best for printed paving.

ADVANTAGES AND USES

- Protection and sealing of exterior stony paving.
- Protection and curing of printed paving.

APPLICATION PROCEDURE

Apply immediately after hardening of surface to be treated, spreading the product directly by means of an atomizer or a short hair roller and making sure to leave a uniform film, without excessive product accumulation and avoiding overly thick layers.

RECOMMENDATIONS

- Do not apply below 5°C nor above 35°C.
- Do not apply when there is a risk of frost, rain, strong wind or direct sunlight or relative humidity above 85%.
- The product is not toxic, dangerous or inflammable under normal handling conditions. The use of special safety measures are not necessary, having to observe at all times those set forth under the Spanish Occupational Hazard Prevention Act.

PACKAGING AND STORAGE

25 l. buckets.

Store up to 2 years in sealed original packaging, sheltered from weather conditions and humidity. Do not expose to temperatures below 5°C nor above 35°C.

TECHNICAL DATA

(Statistical data obtained under standard conditions)	
Aspect	Milky liquid
Density (20°C)	1,00 ± 0,02 g/cm³
Solid content	24,5 ± 0,2 %
Theoretical performance	8-10 m²/ L

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the

FLOORING

PAVILAND® RESINA A4

work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.