



IMPLADUR

Hardening primer

DESCRIPTION

Deep hardening primer to bind substrates prone to disintegrate before applying One-coat Mortars, Cementitious Adhesives, Levelling Mortars, etc.

TECHNICAL CHARACTERISTICS

Solvent-based product containing polyurethane resins.

APPLICATION PROCEDURE

- Apply a coat of IMPLADUR on the substrate to be fixed with a paint roller or a large paintbrush.
- Let dry for 5 hours before applying the mortar.

RECOMMENDATIONS

- Do not apply on plasterboard substrates nor on non-absorbing substrates.
- Do not apply on wet, frozen substrates or in extremely hot weather conditions.
- Avoid the formation of a thin layer due to product accumulation.
- Apply in ventilated areas. Inflammable and volatile product.
- Clean used tools with white spirit.

PACKAGING AND STORAGE

5 and 20 kg bags.
Shelf life: 1 year in sealed original packaging.

TECHNICAL DATA

(Statistical data obtained under standard conditions)	
Colour	Transparent, slightly coloured liquid
Density	0,90 +/- 0,05 gr / cm ³
Approximate Yield	150-200 ml / m ²

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively



ADDITIVES AND PRIMERS

IMPLADUR

to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.

Rev. 2018_05 · This revision cancels all previous ones. Please, obtain the latest version from our web site · www.grupopuma.com · (+34) 957 76 40 40