



IMPLAFIX

Mortar bonding bridge

DESCRIPTION

Adherence primer to promote cement, lime-based mortars and/or plaster-based renders' anchorage on smooth concrete or substrates lacking superficial absorption.

TECHNICAL CHARACTERISTICS

Product containing synthetic resins, mineral fillers and organic and inorganic additives.

ADVANTAGES AND USES

- For indoor and outdoor application.
- Apply on vertical faces and ceilings.

APPLICATION PROCEDURE

- Mix 2 parts IMPLAFIX with 1 part water.
- Apply the mixture with paint roller or large paintbrush.
- Once dry, apply the mortar.

NOTE: Do not apply the mortar more than three days after applying IMPLAFIX.

RECOMMENDATIONS

- Substrates must be clean, dust free, grease, oil, liquid, demolding agents, etc.
- Do not apply when there is a risk of rain or frost.
- Clean the used tools with water right after its use.
- Do not apply the one-coat mortar if IMPLAFIX is still wet.

PACKAGING AND STORAGE

5 and 20 kg buckets.

Shelf life: 1 year in sealed original packaging.

TECHNICAL DATA

(Statistical data obtained under standard conditions)	
Aspect	Colourless liquid
Density	1,05 gr / cm ³
Viscosity	Similar to water
Solubility	Completely soluble in water
Chloride Contents	Free (of)

ADDITIVES AND PRIMERS

IMPLAFIX

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.