



PAVILAND® DESMOLDEANTE

PAVILAND®

MOLD RELEASE

Colored mold release powder



DESCRIPTION

Product in powder form highly recommended to be used on stamped concrete. Avoids adhesion of moulds to concrete improving their release from the stamped concrete.

TECHNICAL CHARACTERISTICS

Product based on demolding or anti-tack agents and high purity inorganic colouring agents.

ADVANTAGES AND USES

- Stamped concrete pavements.
- Variety of colours.
- Excellent anti-tack qualities.

APPLICATION PROCEDURE

- Once the concrete is ready for printing, dust the product with the applicator as usual, covering all the surface.
- Print with the chosen moulds.
- Remove the demolding agent with a water pressure jet three days after application.

RECOMMENDATIONS

Wear gloves, respiratory mask, and protective goggles when applying the product.

PACKAGING AND STORAGE

25 kg plastic-lined paper bags

Shelf life: 2 years in sealed original packaging, sheltered from weather conditions and humidity.

TECHNICAL DATA

(Statistical data obtained under standard conditions)

Aspect	COLOURED powder
Apparent density of powder	0,8 ± 0,1 g/cm ³
Efficiency	100 g/m ²

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the

supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.