



TRADITERM® PERFIL ÁNGULO ALUMINIO CON MALLA

DESCRIPTION

Aluminium perforated reinforcing corner profile, used with the TRADITERM® System. Its easy to apply and the incorporation of the mesh to the profile makes the corner much faster to use.

TECHNICAL CHARACTERISTICS

Aluminium profile with anti alkali fibreglass mesh.

ADVANTAGES AND USES

- Easy to apply.
- Reinforcing corners for use with the TRADITERM® System.
- The incorporation of the profile mesh makes the corner much faster to use.

APPLICATION PROCEDURE

Apply a coat of TRADITERM® mortar on the two surfaces forming the corner, with a layer that incorporates both the profile and the mesh. Next position the profile over the mortar and press gently. With the help of a level, position the profile correctly. Cover the upper layer of the profile with TRADITERM® mortar.

RECOMMENDATIONS

- Leave a 2-3 mm separation distance between the profiles.
- Once the profile has been positioned, leave it to dry for at least 24 hours.

PACKAGING AND STORAGE

Boxes of 100 units (250 linear metres). The profiles must be stored horizontally.

TECHNICAL DATA

(Results obtained in laboratory under standard conditions)

Composition	Aluminium (0.03 mm) and anti alkali fibreglass mesh.
Mesh weight	0.08 kg/m
Profile length	2.5 m

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

TRADITERM® PERFIL ÁNGULO ALUMINIO CON MALLA

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.