


TRADITERM[®] THERM SCREW SF 300 TRADITERM[®] SCREW SF 300



DESCRIPTION

Screw for mechanically fastening TRADITERM[®] 300 Mounting.

COMPOSITION

Zinc-plated steel screw.

FEATURES AND APPLICATIONS

For mechanically fastening TRADITERM[®] 300 Mounting.

INSTRUCTIONS FOR USE

Drill the holes where the SF TRADITERM[®] 300 screws will be used for mechanical fastening element.

CAUTIONS AND RECOMMENDATIONS

The SF TRADITERM[®] 300 Screws must always go through facings and be joined to the actual facade wall. Check the substrate is resistant enough to support the element to be fastened. Always use all 4 SF TRADITERM[®] 300 Screws for fastening TRADITERM[®] 300 Mounting. Respect the maximum load limit to support TRADITERM[®] 300 Mounting.

TECHNICAL DATA

Zinc-plated steel screw.	
Length	100 mm
Ø Drill hole	10 mm
Minimum drill depth	80 mm
Minimum embedded depth of screw	70 mm
Drive	Hexagonal SW13 and Torx T40

NOTE

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

INSULATION

TRADITERM[®] THERM SCREW SF 300

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.

Rev. 2018_05 · This revision cancels all previous ones. Please, obtain the latest version from our web site · www.grupopuma.com · (+34) 957 76 40 40