



TRADITERM® ANCLAJE ESPIRAL

DESCRIPTION

Element for fixing light loads of up to 5 kg to the outdoor TRADITERM® thermal insulation system. Polyamide composite. Easy application. Does not generate thermal bridges.

TECHNICAL CHARACTERISTICS

Polyamide

ADVANTAGES AND USES

- Easy to apply.
- Does not generate thermal flow deviations.
- For fixing light elements to the TRADITERM® System.

APPLICATION PROCEDURE

Once the TRADITERM® System has been applied, on the points where you want to install the light element:

- Position the washer in the threaded point of the spiral anchor and support it over the surface of the system.
- With the aid of a drill, press and insert the Spiral Anchor.
- For the posterior fixing of loads, use exterior Ø type 4-5 mm screws.

RECOMMENDATIONS

- The Spiral Anchor should be fitted after the TRADITERM® System has been applied.
- No pre-drilling is necessary for fitting.
- Maximum Load: 5 kg/unit.

PACKAGING AND STORAGE

Bag of 10 units.

TECHNICAL DATA

(Results obtained in a laboratory under standard conditions)

Composition	Polyamide
Colour	White
Fixing of the part	Outdoor Ø type 4-5 mm screws

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the

FIES/ETICS

TRADITERM® ANCLAJE ESPIRAL

work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.

Rev. 2020_02 . This revision cancels all previous ones. Please, obtain the latest version from our web site . www.grupopuma.com . (+34) 957 76 40 40