



TRADITERM® PERFIL JUNTA DILATACIÓN

DESCRIPTION

PVC profile with anti-alkaline fibreglass mesh and flexible band for joint treatment. Designed as a solution for expansion and structural joints in the support where the TRADITERM® Exterior Thermal Insulation Systems (SATE/ETICS) is going to be installed.

TECHNICAL CHARACTERISTICS

PVC profile with anti alkali fibreglass mesh and flexible band.

ADVANTAGES AND USES

Profile designed as a solution for existing expansion joints in the substrate where the external TRADITERM® Exterior Thermal Insulation Systems (SATE/ETICS) is going to be installed.

APPLICATION PROCEDURE

- Apply MORCEM® THERM mortar over the insulation plates positioned on both sides of the expansion joint.
- Position the fibreglass meshes over the mortar so that the profiles forming these elements are positioned over the corners parallel to the insulation plates forming the joint, in order that both reinforce the corner points of the expansion joint.
- Introduce the elastic band inside the expansion joint.

RECOMMENDATIONS

- Do not clad the existing expansion joints in the substrate with insulation plates. Use the expansion joint profile to resolve this particular point.
- Once the profile has been positioned, leave it to dry for at least 24 hours.

PACKAGING AND STORAGE

Boxes of 25 units. The profile must be stored horizontally.

TECHNICAL DATA

(Statistical data obtained under standard conditions)

Colour	White
Weight	0.22 kg/m
Length	2.5 m

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the

FIES/ETICS

TRADITERM® PERFIL JUNTA DILATACIÓN

work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.

Rev. 2020_02 · This revision cancels all previous ones. Please, obtain the latest version from our web site · www.grupopuma.com · (+34) 957 76 40 40