



PAVILAND® DESMOLDEANTE LÍQUIDO

DESCRIPTION

A liquid release agent used in the execution of stamped pavements to prevent concrete or mortar from adhering to the moulds. This product for pavements allows immediate demoulding after application. Great anti-adhesion power. It prevents the appearance of efflorescences.

TECHNICAL CHARACTERISTICS

Unpigmented liquid product formulated with vegetable and animal fats and oils.

ADVANTAGES AND USES

- It allows immediate demoulding after application Great anti-adhesion power.
- It prevents the appearance of efflorescences.

APPLICATION PROCEDURE

- Once the mortar has been spread over the surface to be marked, apply Paviland Desmoldeante Líquido on both the mortar and the moulds or rollers. This step should be conducted using a sprayer.
- Apply until the base is completely covered.
- Next, use the selected moulds and rollers to achieve the desired finish.
- The waiting times for application may vary depending on the temperature and humidity levels.

RECOMMENDATIONS

- Important: Do not use if the mortar contains excess water.
- Do not apply the product under 5°C nor above 35°C temperature.
- Do not apply under the risk of frost, rain, heavy wind, or direct sun light.
- Do not add any water once the product has been sprayed.
- Use gloves when using the product.
- The molecule contains no chemical groups associated with explosive properties.
- Oxidising properties: Based on its chemical structure, it is incapable of reacting with combustible materials.

PACKAGING AND STORAGE

5 and 25L containers.

Storage up to 24 months in its original closed packaging, protected from weather and moisture. The product must be protected from frost and direct heat exposure.

FLOORING

PAVILAND® DESMOLDEANTE LÍQUIDO

TECHNICAL DATA

Aspect:	Transparent liquid with a characteristic odour
Melting point:	-20°C
Boiling point/range:	156-200°C at 760 mmHg
Ignition point:	39°C Setaflash
Upper/inner flammability or explosive limits:	0.6-7% Volume 25°C/0.5-8.6% Volume 300°C
Vapour pressure:	0.23 kPa at 20°C, 9.3 kPa at 50°C
Relative density:	0.72 g/cm ³ (20°)
Water solubility:	Not soluble
Molecular weight:	146 g/mol
Auto-ignition temperature:	> 200°C
Viscosity:	0.9 cps at 20°C
Approximate performance:	60-80 ml/m ² - 15 m ² /l approx.

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.