



MORCEM® ANTIGOTERAS

MORCEM®

ANTI-DRIP

DESCRIPTION

Waterproof covering with high elasticity and flexibility. Suitable for avoiding water leakage on terraces, rooftops, roof tiles, expansion joints, downpipes, etc. For repairing areas with existing cracks, or with a tendency to split. It provides continuous coverage capable of preventing water leakage and the subsequent problems deriving from humidity.

ADVANTAGES AND USES

- Excellent water tightness and provides protection against liquids in general.
- Resistant to rain water.
- Strong resistance to traction and elongation of the breakage.
- Good product homogenisation and easy to apply.
- Weather and UV resistant film.
- High resistance to abrasion.
- Good filling of cracks and resistant to micro-cracking.

SUITABLE SUBSTRATES

NEW SURFACES

- The surfaces to be painted must be dry and free from dust, soil, moss, efflorescence, nitrate, grease, etc.
- Remove any dust, grease and other contaminants.
- Apply the paint according to the instructions.

OLD SURFACES

- Remove any possible contaminating mould, loose paintwork and other building materials with bleach or another suitable product.
- Treat the efflorescence or nitrate with a diluted acid product, rinse, and leave to dry. It could be advisable to treat the surface with ANTISALMOR.
- Apply a prior coat of FIJAMOR to substrates in a bad condition, with a lack of cohesion or with humidity problems.
- Cracks or breaks larger than 1 mm must be repaired preferably with mortar, or a mixture of 1 part MORCEM ANTIGOTERAS and 4 parts dry sand.
- Sand and level the slopes or uneven surfaces to be painted to avoid any possible waterlogging.
- Apply the paint according to the instructions.

APPLICATION PROCEDURE

- Shake product until perfectly mixed.
- Dilute the first coat with water (5-10%).
- Apply the second and following coats undiluted, in a cross direction to the previous layer.
- The product can be applied with a brush, roller or spray gun after first shaking the diluting it, respectively.

ACRYLIC RUBBER

MORCEM® ANTIGOTERAS

RECOMMENDATIONS

- Tools should be cleaned with water before the paint dries.
- Do not apply at temperatures lower than 5°C
- Do not apply with relative humidity higher than 85%, nor to wet substrates.
- Do not apply if there is any possibility of rain or frost.
- Store in a cool dry place.

PACKAGING AND STORAGE

15 litre packs. Store in sealed original packaging, sheltered from weather conditions and humidity and away from intense cold and heat: Shelflife: 2 years.

TECHNICAL DATA

Binder	Styrenated acrylic
Solvent	Water
Fixed matter (weight)	52%+/- 1
Specific weight	1.25 kg/L
Viscosity (22°C)	90 dPas +/- 20
Theoretical performance	1.2-1.5 m²/l
Drying time	To the touch 2-3 hours. Total < 24 hours
Repaint interval	At least 12 hours, according to atmospheric conditions
Finish	Semi Matte
Colours	White, Red, Terracotta, Green and Grey

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.