



TRADITERM® PERFIL TERMINACIÓN VENTANA TRADITERM® WINDOW FINISHING PROFILE

DESCRIPTION

Profile for connection and final finishing between the different TRADITERM® (EWI/ETICS) Systems and the existing carpentry on the façade.

TECHNICAL CHARACTERISTICS

PVC profile with anti-alkali fibreglass mesh.

ADVANTAGES AND USES

- Easy and quick to apply.
- Connection profile for the Traditerm Systems (EWI/ETICS) with door and window frames.

APPLICATION PROCEDURE

- Apply a layer of TRADITERM mortar over the surface of the insulation panel adjacent to the window or door frame.
- Fix the profile supporting the mesh over the mortar and the rest of the profile over the frame.
- Softly press the mesh over the mortar with a trowel and cover the mesh with the excess mortar.
- The profile has a strip of self-bonding plastic which is used for provisionally fixing a protective paper to avoid dirtying the carpentry during the application of products. Its use is optional. Once the application has been completed, remove the plastic strip by pulling it.

RECOMMENDATIONS

- Once the profile has been positioned, leave it to dry for at least 24 hours.
- Use the protective mechanism to avoid staining the carpentry.

PACKAGING AND STORAGE

Boxes of 30 units to 72 linear metres.
The profiles must be stored horizontally.

TECHNICAL DATA

Composition	PVC and Fibreglass with anti-alkali treatment
Profile length	2.4 m

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the

conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.