



PAVILAND® CAUCHO

Crushed rubber recycled with different sizes and colors.

DESCRIPTION

Crushed rubber from recycled tire, with different sizes and colors. Used for the implementation of continuous and flexible pavement manufactured in situ.

ADVANTAGES AND USES

- Continuous and flexible pavement
- Children's playgrounds
- Recreational areas
- Grates
- Swimming pool environments
- Sports centers

APPLICATION PROCEDURE

BASE COAT OF CRUSHED BLACK RUBBER

- Cement base or stable support.
- Preparation: The support must be clean and stable.
- Primer: It is necessary to apply a primer band TEXTUREFIX-120 or RESINA AGLUTINANTE AROMATICA along the perimeter of the Park and on the legs of the games.
- In a mixer or a bucket, mix (preferably mechanical mixer) black rubber with 9% of RESINA AGLUTINANTE AROMATICA, until it is completely impregnated with resin.
- Demarcate the area with the required height. In case of pavements for playgrounds, the thickness of the coat will be depending on the height of the games, and must comply with regulations EN1177.
- Apply the product with a trowel of steel or similar, compacting it up to equalizing it at a height of the ruler.
- Let's dry 6 hours

FINISH COAT WITH CRUSHED ENCAPSULATED RUBBER

- To demarcate and create the different decorative zones, it is recommended to use a semiflexible naked cable of copper, to delimit the colors during the application. The cable will have to be fixed to the rubber base with a few metallic hooks.
- Mix the encapsulated rubber (colored) with 12% of RESINA AGLUTINANTE AROMATICA or RESINA AGLUTINANTE ALIFATICA.
- Apply the product and compact it with the same steel trowel until the height of the cable (1 cm).
- Once applied the whole surface, it is recommended to finish the compaction with a gardening roller. After 6 hours, it will be possible to pass along the pavement.

PACKAGING AND STORAGE

Bags of 25 kg.

TECHNICAL DATA

Colours	Colores Gama (Amarillo Ocre 300, Marrón medio 400 y Rojo 204)
	Colores especiales (Azul Cielo 666, Azul eléctrico 665, Azul Intenso 662, Gris 100, Marrón Claro 459, Verde Militar 508, Negro acabado)
	Colores Plus (Amarillo Canario 780, Naranja Butano 218, Rojo 200, Rosa Fucsia 700, Blanco 109)
	Colores Luz (Verde Hiedra 509, Verde Pradera 514, Blanco Nuclear 105, Amarillo 329)
PARTICLE SIZES	Black rubber: 4-8 mm
	Encapsulated rubber: 1-3 mm

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.