

# PAVILAND® ARQ COLOR



Pigment for Paviland® ARQ Acabado

## DESCRIPTION

Pigment for Paviland® ARQ range.

## COMPOSITION

Dispersion of organic and inorganic pigments in water

## FEATURES AND APPLICATIONS

- Great purity and finesse
- Easy to incorporate
- High coloring power
- Pigment for colouring Paviland® ARQ Acabado and in case of intense colours for Paviland® ARQ Base.

## INSTRUCTIONS FOR USE

- Shake the product before mixing
- Add to Paviland® ARQ, according to the system requirements, until the total homogenization of the color.

## CAUTIONS AND RECOMMENDATIONS

- Prolonged storage can lead to phase separation due to the different densities of the components. If this happens, the paste should be shaken conveniently until its homogenization
- Protect from extreme cold and heat
- The colours on our catalogue are indicative, and the shade may change depending on the conditions of application and the coats of sealant. Some variation in colour uniformity may also occur during the hardening process of the product. In case of high aesthetic demands it is advisable to make a previous sample.

## YIELD

1 pot per pack of Paviland ARQ Acabado except special marked colors

## PACKAGING

0.5 kg pots  
Shelf life: 2 years in sealed original packaging, sheltered from weather conditions and humidity.

## NOTE

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the

# FLOORING LINE

## PAVILAND® ARQ COLOR

work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.