

PAVILAND® CUARZO COLOR

Coloured quartz aggregates.

DESCRIPTION

Quartz aggregate of different colours for industrial decorative pavements: anti-slipping and self-levelling multilayer systems.

TECHNICAL CHARACTERISTICS

Siliceous nature aggregates.

ADVANTAGES AND USES

- Colour is not affected by UV light.
- High chemical and mechanical resistance.
- Solvents, emulsions and resin resistant colours.
- Wide range of colours and combinations.
- Continuous decorative industrial pavements.
- Production of anti-slipping and self-levelling multilayer floors from the PAVILAND DECOR range.
- Final claddings of easy maintenance and easy to clean.
- Great durability.
- Other uses: decorations and fillings, gardening, landscape, etc.

PACKAGING AND STORAGE

25 Kg packaging.

Please consult its availability and minimum order in Big Bag. Check the wide range of colours and combinations.

Storage: dry places and away from open sky.

TECHNICAL DATA

(Statistic results obtained in standard conditions).

Aspect	Coloured Arid
Apparent density	1,45 kg/dm ³
Real Density	2,65 kg/dm ³
Maximum content of humidity	0.25 %
Granulometry (*)	0,3 – 0,7
Chemical composition	98,5 % SiO ₂ (quartz silica)
	< 1,3 % Al ₂ O ₃
	0,03 % Fe ₂ O ₃
	0,05 % TiO

(*)Please consult for other granulometry availability.

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

FLOORING

PAVILAND® CUARZO COLOR

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.

Rev. 2018_05 - This revision cancels all previous ones. Please, obtain the latest version from our web site - www.grupopuma.com - (+34) 957 76 40 40