



TRADITERM® PERFIL ÁNGULO ARISTA VIVA

DESCRIPTION

PVC profile, designed for corner reinforcement in external thermal insulation Traditerm Systems(SATE/ETICS). Its easy to apply and the incorporation of the mesh to the profile, makes the execution of the corner faster.

TECHNICAL CHARACTERISTICS

PVC profile with fibreglass mesh with anti-alkali treatment.

ADVANTAGES AND USES

- Easy to apply.
- Reinforcement for corners in TRADITERM Systems (SATE/ETICS).
- The incorporation of the mesh to the profile, makes the execution of the corner faster.

APPLICATION PROCEDURE

Apply Traditerm mortar layer on both the surfaces that define the edge, from the profile till the mesh. Place the profile on top of the mortar and press gently. With the help of a level, place the profile correctly. With the surplus Traditerm mortar, resulting from pressing the profile with the trowel, cover the mesh and the profile. The front part of the tab that stands out of the profile, forms the angle of the corner and therefore, it remains seen. Even if the mesh is fully covered, the grids should be marked.

RECOMMENDATIONS

- Joints between profiles should not coincide with joints between insulation panels.
- Once the profile has been placed, let it dry for 24 hours minimum.

PACKAGING AND STORAGE

100 units box. 250 lineal meters.
Profiles should be stocked up in horizontal position.

TECHNICAL DATA

Composition	PVC and fibreglass with anti-alkali treatment
Profile length	2.5 m
tab length	4 mm

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.