



TRADITERM® TAPA AISLANTE EPS

DESCRIPTION

Expanded polystyrene cover to fill in the gap left by the corona STR in the insulating panel when TRADITERM® TACO DE ANCLAJE STR U 2G is installed. Levelling of TRADITERM® PANEL EPS. Get the TRADITERM® TACO DE ANCLAJE STR U 2G hidden inside the insulation panel.

TECHNICAL CHARACTERISTICS

Expanded polystyrene

ADVANTAGES AND USES

- This piece is used in the Traditerm EPS (SATE/ETICS) System, for Traditerm Taco
- the Anclaje STR U 2G installation, according to the Insulating Interior method.
- Levelling of the Traditerm Panel EPS insulating plaques.
- Make sure Traditerm Taco de Anclaje STR U 2G is hidden in the interior part of the insulating panel.

APPLICATION PROCEDURE

Place the anchor peg on the hole done and screw it towards the inside with the help of the "Traditerm Kit Corona STR".

Once the peg has been introduced in the insulator, place the Traditerm Tapa Aislante EPS".

RECOMMENDATIONS

In order to make the hole in the Traditerm Panel EPS insulating plaque, help yourself with the corona STR tool.

PACKAGING AND STORAGE

100 units box.
Keep away from open air and sun radiation.

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively

FIES/ETICS

TRADITERM® TAPA AISLANTE EPS

to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.

Rev. 2020_02 · This revision cancels all previous ones. Please, obtain the latest version from our web site · www.grupopuma.com · (+34) 957 76 40 40