



FIJAMOR

Surface consolidating sealant

DESCRIPTION

Primer indicated to favour the anchorage of paints and coatings in restoration. It regularises the absorption of the foundations and superficially consolidates inconsistent foundations.

TECHNICAL CHARACTERISTICS

Emulsion of acrylic copolymers of very small particle size, in aqueous suspension, free of organic solvents.

ADVANTAGES AND USES

- Good capacity for penetrating foundation.
- Good adhesion
- Improves weak and porous foundations.
- Inside and outside application

SUITABLE SUBSTRATES

- Conventional foundations based on hydraulic binders, ceramic pieces, gypsum, perlite.
- Sanitize the foundation in possible areas lacking cohesion or little resistance.
- Get rid off loose pieces of masonry and paintwork.
- Remove possible traces of dust, release agents, organic products and other contaminants.

APPLICATION PROCEDURE

- Stir until the product is homogenised.
- Dilute with two or three parts of water depending on the absorption of the foundation.
- Apply by brush, roller or spray on the foundation.
- If the foundation is very absorbent, it may be necessary to apply multiple layers. Wait for one coat to be absorbed before applying the next coat.
- Time till dry to touch: 60 minutes
- The cleaning of the tools shall be carried out with water immediately after use.

RECOMMENDATIONS

- Do not apply below 5°C nor above 30°C.
- Do not apply where there is a risk of freezing, rain, strong winds or direct sun.
- Do not use on surfaces with very low or no absorption.
- Prevent film formation to fulfil the surface consolidating function of Fijamor.
- Do not use on wet surfaces that hinder the absorption of Fijamor by the foundation.

PACKAGING AND STORAGE

5 and 25L containers.

Storage stability in closed original packaging, protected from weather and humidity and protected from intense cold and heat: 2 years.

TECHNICAL DATA

Statistical results obtained under standard conditions	
Thinner	Water
Specific weight	1,01 Kg/L

ADDITIVES AND PRIMERS

FIJAMOR

LEGAL DISCLAIMER

Performance	6-8 m ² /L according to foundation
Dry to the touch	60 min
Repainting time	8 Hours min

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.