

PAVILAND® RENOVEX



DESCRIPTION

Universal pigment dispersion free from solvents base on additives related to pigments.

APPLICATION
PROCEDURE

Add to adequate paint, varnish or sealed top, homogenize the components and apply it.

RECOMMENDATIONS

- Keep away from children.
- Work with adequate gloves and protective glasses; and in case of chemical splash or eye contact, wash with abundant water and visit your ophthalmology as soon as you can.
- Use in places with good ventilation. In the event of not having proper ventilation, please use adequate breathing equipment.
- Do not throw any waste through the drainpipe.

PACKAGING AND
STORAGE

1 Kg packaging.
6 months storage in its original packaging, indoors and away from humidity.

TECHNICAL DATA

(Statistic results obtained in standard conditions)

Aspect	Plaster
Density	1,1 - 1,3 gr/cm ³ Aprox.
Maximum particle	≤ 20
Pigment	30%
Viscosity	< 500 cps
Light (1-8 Scale)	
Full tone	7-8
Reduced tone (1:3)	8
Outdoors (1-5 Scale)	
Full tone	5
Reduced tone (1:3)	4-5
Stability	
to acids	2% HCl - Scale (1-5) : 5
to alkalis	2 % NaOH - Scale (1-5) : 5
Consumption	10% in weight (depending on the opacity)

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions

carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.