

UNOFIN ACRYLIC MOSAICO



DESCRIPTION

Ready to use synthetic mineral render for waterproofing and decorating façades and indoor walls, especially designed for reinforcing skirting boards (baseboards) in the WaAce external thermal insulation system. Outdoor and indoor application. Decorative finish for WaAce System (EIFS). Formulated with additives that prevents and delay the apparition of algae and molds.

TECHNICAL CHARACTERISTICS

Product based on acrylic resins, crushed natural stone, mineral pigments and organic and inorganic additives.

ADVANTAGES AND USES

- Ready to use.
- High surface hardness.
- Resistant to weather conditions.
- Resistant to mold and algae.
- Waterproof.
- Permeable to water vapor, allowing the substrate to breathe.
- Quick and simple application.
- Compatible with most substrates.
- Resistant to aging, city atmosphere and UV radiation.
- Excellent adhesion to usual construction surfaces.
- Washable.
- Ideal for dealing with the area of skirting boards (baseboards) and frames around windows and doors in façades.

SUITABLE SUBSTRATES

- Compatible with mineral mortars, concrete, one-coat mortars and plasters.
- WaAce EIFS ready to use of the final decorative finish.
- Not compatible with fresh lime renders, resins or varnishes, distemper, lime or silicate paints, on substrates that are already painted.
- The supports must be clean, free of dust, loose particles, remains of old paints, oils, fungi, molds and other microorganisms, etc

APPLICATION PROCEDURE

- Mix until the material is homogenous.
- The product is ready to use, applications with a stainless steel trowel.
- Spread the product on the substrate, and pass the trowel successively over the applied surface, always in the same direction, to get a flat surface completely covered by UnoFin ACRYLIC MOSAICO.
- Clean work tools with water immediately after use. Remove dry remains with turpentine paint solvent.
- The substrates must be sound clean, free of dust, loose particles, residues of old paints, oils, etc.
- Use consolidating primer on low cohesion substrates. Always prime with UnoFin ACRYLIC BASECOAT.

UNOFIN ACRYLIC

UNOFIN ACRYLIC MOSAICO

RECOMMENDATIONS

- Do not apply at temperatures below 5°C or above 35°C, under direct sunlight, rain or risk of frost.
- Do not apply if humidity is greater than 70%, either in terms of the environment or the surface, nor if it is predicted to rain in the coming days.
- Do not apply on horizontal substrates (floors) or sloped less than 45°.
- Protect the upper part of the render to avoid rain water penetration.
- Being the product's finish dependent on the mix of its natural composed stones, its results may vary.
- To avoid small colour variations order all the necessary product in a single order and do not mix different batch numbers in a single working area.
- When using spray gun keep pressure, and wall distance constants to avoid finishing variations.
- Low temperatures and high humidity make it harder for the Morcemcrl Mosaico to dry, thus lengthening the drying time.
- Protect surrounding areas thoroughly. Clean with water any spillage before drying.

PACKAGING AND STORAGE

UnoFin ACRYLIC MOSAICO comes in 20 kg plastic buckets.

Shelf life: 2 years in sealed original packaging, store in fresh and dry places. Avoid exposure to temperatures below 5°C or above 30°C. Sheltered from weather conditions.

TECHNICAL DATA

(Statistical data obtained under standard conditions)

Specific weight	1.7 kg/L
Yield	4 – 5 kg/m ²
Drying time	2 hours at 25°C and 50% humidity
Colors on request	Consult range

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by PIDILITE GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

PIDILITE GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of PIDILITE GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by PIDILITE GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.