



PAVILAND® RESINA MT

DESCRIPTION

Liquid resin in a solvent medium, suitable for sealing and protecting flooring. It is made from polymers based on methacrylate dissolved in aromatic solvents. It hardens through the evaporation of solvents and works by increasing the cohesion of the flooring, creating a decorative and highly resistant layer that enhances the properties of the flooring and increases its durability.

ADVANTAGES AND USES

- A finish layer of exceptional hardness that prevents the degradation of the flooring.
- The finish layer offers exceptional abrasion resistance and toughness.
- It increases impact resistance, resulting in an excellent surface finish.
- It significantly enhances the protection of the flooring in areas with vehicular traffic.
- It has a great sealing power, avoiding the appearance of efflorescences.
- It improves abrasion and wear resistance, providing greater durability to the substrate.
- It provides a walkable finish with excellent shine retention, enhancing the natural appearance of the flooring.
- Due to its composition, the finished product film does not turn yellow over time.

APPLICATION PROCEDURE

- It should be applied immediately after the surface to be treated has hardened and once the release agent has been thoroughly removed. The product should be distributed evenly using a sprayer, air gun, or roller, ensuring a uniform film without excessive product buildup, and avoiding the application of thick layers.
- The thickness of the layer once dry should be around 30-40 microns and can be recoated after a minimum drying interval of 6 hours at 20°C, depending on the shine level required.
- The cleaning of the tools used should be done with xylene or a universal solvent.

RECOMMENDATIONS

- The substrate must be clean, free of cracks, completely dry, and devoid of release agents, dust, loose materials, grease, or any elements that could impair the adhesion of the product.
- The surface must be dried otherwise pathologies may defects or issues may occur in the resin film.
- Do not apply when there is a risk of frost, rain, intense winds, direct sunlight, or relative humidity above 85%, as these conditions can affect drying and cause irregularities in the final appearance of the application.
- In enclosed spaces, adequate ventilation must be provided during the application and drying time of the product.
- At all times, the conditions stipulated in the Occupational Risk Prevention Law must be observed.
- Toxic by inhalation, ingestion, and contact with skin or eyes.
- Do not eat or smoke when manipulating the product.
- Keep away from heat sources. Store in a protected and well-sealed container.
- When applying with an air gun, do so only in well-ventilated areas and use respiratory protection if necessary.
- It is necessary to have membranes, plastic sheets, or vapour barriers in place before pouring the concrete to provide an impermeable element that isolates the flooring from moisture coming from the ground.
- Do not apply the product at ambient temperatures below 5°C or above 35°C.

PACKAGING AND STORAGE

FLOORING

PAVILAND® RESINA MT

25L containers

Store in its original closed packaging. In fresh and dry places, away from open air and direct sun light. Avoid extreme weather conditions (not lower to 5°C nor above 35°C) 2 years.

Rev. 24_02 · This revision cancels all previous ones. Please, obtain the latest version from our web site · www.grupopuma.com · (+34) 957 76 40 40

TECHNICAL DATA

Alloy	Polymethyl methacrylate
Solvent	Organic solvent
Density at 20°C	0.90 +/- 0.02 g/cc
Solubility	In most aromatic hydrocarbons
Finish	Semi-shiny
Approximate performance	8-10 m²/l
Solid content	27.5 +/-1.0%
Category according to R.D 227/2006	A/h (BD)
Abrasion resistance Taber (H22/100g/200 cycles) cycles)	185mg

LEGAL DISCLAIMER

Instructions given on how to use the product are given based on our tests and knowledge and do not imply any commitment from GRUPO PUMA and do not exempt the user from checking and verifying the products before using them. Claims must be presented with the original packaging to allow an adequate traceability.

GRUPO PUMA is not responsible, under any circumstances, for the application of its products or constructive solutions by the applicator company or other subjects involved in the application and / or execution of the work in question, limiting the responsibility of GRUPO PUMA exclusively to possible damages attributable directly and exclusively to the products supplied, individual or integrated into systems, due to failures in their manufacture.

In any case, the creator of the work project, the technical management or person in charge, or subsidiarity the application company or other people involved in the application and / or execution of the work in question, must ensure the suitability of the products. Taking always into account the substrates and any pathologies that may occur in the workplace itself.

The values of the GRUPO PUMA products or construction solutions, mentioned in the UNE norm or in any other, exclusively refer to the stipulated conditions. They all refer to specific characteristics on the substrates (humidity, temperature, etc.) without being required for tests obtained under different conditions.