

DECLARATION OF PERFORMANCES

Nº: 501863-01

1. **Product:**
PAVILAND SOLERA R AUTONIVELANTE

2. **Manufacturer:**
GRUPO PUMA ESPAÑA S.L con domicilio en:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com

3. **Intended use:**
Fast setting, self-levelling screed mortar, type CT C25 F5 B1,5, for bonded interior screeds up to 50 mm and unbonded up to 100 mm.

4. **Evaluation system :**
4

5. **Declared performances :**

Essential characteristics	Performances	Harmonised technical specification
Reaction to fire	Type E	EN 13813:2014
Emission of corrosive substances	CT	
Water permeability	NPD	
Water vapor permeability	NPD	
Compressive strength	C25	
Flexural strength	F5	
Tensile strength	B1,5	
Wear Strength	NPD	
Acoustic insulation	NPD	
Acoustic absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Hazardous substances	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2, in accordance with Regulation (EU) No 305/2011.

Signed by and on behalf of the manufacturer:
Place and Date of issue: Córdoba, 14/07/23



Technical Director:



GRUPO PUMA ESPAÑA, S.L
 Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
 14014 CÓRDOBA

16

PAVILAND SOLERA R AUTONIVELANTE

Nº: 501863-01

EN 13813

Fast setting, self-levelling screed mortar,
 type CT C25 F5 B1,5, for internal screeds bonded up to 50 mm and
 unbonded up to 100 mm.

Reaction to fire	Type E
Emission of corrosive substances	CT
Compressive Strength	C25
Flexural strength	F5
Tensile strength	B1,5
Hazardous substances	See safety datasheet