

DECLARATION DE PERFORMANCES

Nº: 801436-1

1. **Product:**
MORCEMSEC PROYECTABLE INTERIOR GRIS
2. **Manufacturer:**
GRUPO PUMA SL, located in:
Avda Agrupación Córdoba 17,
14014 Córdoba
www.grupopuma.com
3. **Intended use:** Mortar for plaster for current use GP CSIII W0, for the realization of projected interior plastering up to 1.5 cm thick.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN 998-1:2018
Water absorption	W0	
Diffusion coefficient of water vapour	PND	
Thermal conductivity : ($\lambda_{10,dry}$)	PND	
Adhesion	$\geq 0.3 \text{ N/mm}^2$ Shape breakage B	
Durability	PND	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2, in accordance with Regulation (EU) No 305/2011.
Signed by and on manufacturer behalf
Place and date of issue: Córdoba, 02/06/2022



Technical director: José A. Ferre Martínez



GRUPO PUMA S.L
Avda. Agrupación Córdoba 17
14014 Córdoba

18

MORCEMSEC PROYECTABLE INTERIOR GRIS
Nº: 801436-1
EN 998-1

Mortar for plaster for current use GP CSIII W0, for the realization of projected interior plastering up to 1.5 cm thick.

Reaction to fire

Type A1

Water absorption

W0

Adhesion

≥ 0.3 N/mm² Shape breakage A/B