

## DECLARACION OF PERFORMANCES

### Nº: 100157-159

1. **Product:**  
PEGOLAND FLEX GRIS
2. **Manufacturer:**  
GRUPO PUMA SL with address at:  
Avda. Agrupación Córdoba, 17  
14014 Córdoba (Córdoba)  
www.grupopuma.com
3. **Intended use:**  
Improved cementitious adhesive, deformable with reduced sliding and extended open time, Pegoland Flex Gris, For the placement of interior and exterior floorings, interior and exterior coverings, for facades, radiant heating floors, cold rooms, large surface floorings and overlaps, swimming pool coverings and placement on cementitious waterproofing, adhesion of all types of ceramic pieces, porcelain stoneware, marble, granite and natural stone.
4. **Evaluation system:**  
3
5. **Notified bodies:**  
They have carried out the type tests nº 79617 dated November 2004, nº 2504450 dated July 2005, nº 2525029 dated December 2006, nº 2811079 dated April 2008, nº 2829489 dated October 2009, nº0201/01/2011/005919 dated July 2011 in CEMOSA nº 1377 (Málaga) and nº 5029469, 5026639 dated July and September 2005, nº 31212764 dated August 2006, nº 08/32308143 dated July 2008, nº 08/32312894, 08/32311901, dated February 2009 in APPLUS nº 0370 (Barcelona) obtaining the same product results for all factories.
6. **Declared performances:**


Essential characteristics	Performances	Harmonized technical specifications
<b>Reaction to fire:</b>	Class E	EN-12004:2007+A1:2012
<b>Adherence:</b> - Initial tensile adhesion	$\geq 1\text{N/mm}^2$	
<b>Durability:</b> - Tensile adhesion after immersion in water - Tensile adhesion after thermal aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
<b>Hazardous substances:</b>	See Safety Data Sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6  
This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.  
Signed by and on behalf of the manufacturer:

Place and Date of issue: Málaga, 17/09/2019



Technical director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA SL Avda. Agrupación Córdoba, 17, 14014 Córdoba (Córdoba) 04	
<b>PEGOLAND FLEX GRIS</b> <b>Nº: 100157-159</b> <b>EN 12004: 2007 + A1:2012</b>  Improved cementitious adhesive, deformable with reduced sliding and extended open time, Pegoland Flex Gris, For the placement of interior and exterior floorings, interior and exterior coverings, for facades, radiant heating floors, cold rooms, large surface floorings and overlaps, swimming pool coverings and placement on cementitious waterproofing, adhesion of all types of ceramic pieces, porcelain stoneware, marble, granite and natural stone.	
<b>Reaction to fire:</b>	Class E
<b>Adherence:</b>	
- Initial tensile adhesion:	$\geq 1\text{N/mm}^2$
<b>Durability:</b>	
- Tensile adhesion after immersion in water	$\geq 1\text{N/mm}^2$
- Tensile adhesion after thermal aging	$\geq 1\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$
<b>Hazardous substances:</b>	See safety data sheet