

DECLARATION OF PERFORMANCES N°: 501867

1. Product:

PAVILAND INDUSTRIAL 25 AUTONIVELANTE

2. Manufacturer:

GRUPO PUMA ESPAÑA SL located in: Avda. Agrupación Córdoba, 17 14014 CÓRDOBA www.grupopuma.com

3. Intended use:

- Self-leveling cementitious floor type CT C35 F7 A15 B1, for industrial indoor use in thicknesses ranging from 5 to 25 mm.
- 4. Evaluation system:
 - 4

5. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN 13813:2014
Emission of corrosive substances	СТ	
Water permeability	NPD	
Water vapor permeability	NPD	
Compression strength	C35	
Flexural strength	F7	
Wear resistance	A15	
Tensile strength	B1	
Acoustic insulation	NPD	
Acoustic absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Hazardous substances	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2, in accordance with Regulation (EU) No 305/2011.

Signed by and on behalf of the manufacturer: Place and Date of issue: Córdoba, 30/03/23

Technical Director: Jose A. Ferre Martínez



(F		
GRUPO PUMA ESPAÑA S.L		
Avda. Agrupación Córdoba, 17 14014 CÓRDOBA		
23		
PAVILAND INDUSTRIAL 25 AUTONIVELANTE		
Nº: 501867		
EN 13813		
Self-leveling cementitious floor type CT C35 F7 A15 B1, for industrial indoor use in thicknesses ranging from 5 to		
25 mm.		
Reaction to fire	Туре А1	
Emission of corrosive substances	СТ	
Compression strength	C35	
Flexural strength	F7	
Wear resistance	A15	
Tensile strength	B1	