

DECLARATION OF PERFORMANCES

Nº: 100020

1. **Product:**
PEGOLAND SUPERFLEX BLANCO
2. **Manufacturer:**
GRUPO PUMA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:** Highly deformable improved cementitious adhesive with reduced slip and extended open time, PEGOLAND SUPERFLEX BLANCO, for gluing of floors and coatings, interior and exterior. Special for facades, large surface flooring, radiant heating floors, overlays, cold rooms, swimming pools and cementitious waterproofing.
4. **Evaluation system:**
3
5. **Notified bodies:** Type tests nº 001-22/028186/1, 001-22/028185/1 and 001/028188/1 of September 2022 have been carried out in CEMOSA nº 1377 (Malaga).
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	≥ 1 N/mm ²	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	≥ 1 N/mm ² ≥ 1 N/mm ² ≥ 1 N/mm ²	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.
Signed by and on manufacturer behalf.
Place and date of issue: Malaga, 15/09/2022



Technical director: José A. Ferre Martínez



1377

GRUPO PUMA SL
Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba)
22

PEGOLAND SUPERFLEX BLANCO
Nº: 100020
EN-12004:2007+A1:2012

Highly deformable improved cementitious adhesive with reduced slip and extended open time, PEGOLAND SUPERFLEX BLANCO, for gluing of floors and coatings, interior and exterior. Special for facades, large surface flooring, radiant heating floors, overlays, cold rooms, swimming pools and cementitious waterproofing.

Reaction to fire: Type E

Adhesion:

- Initial tensile adhesion strength $\geq 1 \text{ N/mm}^2$

Durability:

- Tensile adhesion after water immersion $\geq 1 \text{ N/mm}^2$

- Tensile adhesion after heat aging $\geq 1 \text{ N/mm}^2$

- Tensile adhesion after freeze/thaw cycles $\geq 1 \text{ N/mm}^2$

Hazardous substances: See safety datasheet