

## DECLARATION OF PERFORMANCES

### Nº: 800002-1

**1.- Product:** MORCEMSEC CAPA GRUESA BLANCO MANUAL

**2.-Intended use:** Dry cladding mortar, CR CSIV W2 for outdoor plastering, up to 2 cm. Impermeable to rainwater.

**3.-Manufacturer:** GRUPO PUMA SL with registered address at: Avda. Agrupación Córdoba 17,14014 Córdoba [www.grupopuma.com](http://www.grupopuma.com)

**4.-Evaluation System:** 4

**5.-Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1	EN-998-1:2010
Water absorption	W2	
Diffusion coefficient of water vapour	$\mu \leq 15$	
Thermal conductivity $:(\lambda_{10,dry})$	NPD	
Adhesion	$\geq 0.3 \text{N/mm}^2$ Breakage method A/B	
Durability	NPD	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5. This declaration of features is issued under the sole responsibility of manufacturer stated in point 3.

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 28/05/2019





GRUPO PUMA SL  
Avda Agrupación Córdoba 17  
14014 Córdoba  
05  
Nº: 800002-1

**EN 998-1**

**MORCEMSEC CAPA GRUESA BLANCO MANUAL**

Dry cladding mortar, CR CSIV W2 for outdoor plastering, up to 2 cm. Impermeable to rainwater.

- Reaction to fire:** Class A1
- Water absorption:** W2
- Diffusion coefficient of water vapour:**  $\mu \leq 15$
- Adhesion:**  $\geq 0.3 \text{N/mm}^2$  Breakage method A/B