

DECLARATION DE PERFORMANCES Nº: 230042

1. **Product:**
MORCEMDRY SF PLUS
2. **Intended use:** Coating mortar for surface protection, flexible two-component for waterproofing concrete, with a minimum layer thickness of 2mm. Principles 1-2 and 8. Methods 1.3; 2.2 and 8.2
3. **Manufacturer:**
GRUPO PUMA SL, located in:
Avda Agrupación Córdoba 17,
14014 Córdoba
www.grupopuma.com
4. **Evaluation system:**
2+4
5. **Notified bodies :**
Applus no. 0370, Production control conformity certificates no. 0370-CPR-2578 and no. 0370-CPR-4693
6. **Declared performances:**

Essential characteristics	Performance	Harmonized standards	Harmonised technical specification
CO2 permeability	Sd>50m	EN 1062-6	EN-1504-2: 2004
Water vapour permeability	Classe I	ISO 7783-1 ISO 7783-2	
Capillary absorption & permeability to liquid water	≤0.1Kgm-2h -0.5	EN 1062-3	
Thermal compatibility	Complies	EN1062-11	
Adhesive strength by tensile test	>1.5N/mm2	EN 1542	
Hazardous substances	See safety datasheet		

The performances of the product identified in point 1 comply with the performance declared in point 6.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 3, in accordance with Regulation (EU) No. 305/2011.
Signed by and on manufacturer behalf
Place and date of issue: Córdoba, 22/07/22



Technical director: José A. Ferre Martínez



0370

Avda. Agrupación Córdoba 17
14014 Córdoba
16
Nº: 230042

0370-CPR-2578
0370-CPR-4693

EN 1504-2

MORCEMDRY SF PLUS

Coating mortar for surface protection, flexible two-component for waterproofing concrete, with a minimum layer thickness of 2mm.

CO2 permeability	Sd>50m
Water vapour permeability	Classe I
Capillary absorption & permeability to liquid water	≤0.1Kg _m -2h ^{-0.5}
Thermal compatibility	Complies
Adhesive strength by tensile test	>1.5N/mm ²