

DECLARATION OF PERFORMANCES

Nº: 600770-01

1. **Product:**
MORCEMDUR RASPADO
2. **Manufacturer:**
GRUPO PUMA SL located in:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:** Monolayer plaster mortar OC CSIII W2, for façade finishing and rain protection with finish scraping
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN 998-1:2018
Water absorption	W2	
Water permeability after climatic cycles conditioned	$\leq 1 \text{ ml/cm}^2$ after 48 hours	
Diffusion coefficient of water vapour	$\mu \leq 15$	
Thermal conductivity ($\lambda_{10, \text{seco}}$)	PND	
Adhesion after climatic cycles conditioned	$\geq 0,3 \text{ N/mm}^2$ Form A/B breakage	
Durability	Evaluation based on provisions valid in the intended place of use of the mortar	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2,
in accordance with Regulation (EU) N° 305/2011.

Signed by and on manufacturer behalf.
Place and date of issue: Cordoba, 18/11/2022



Technical director: José A. Ferre Martínez



GRUPO PUMA S.L
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
18

MORCEMDUR RASPADO
Nº: 600770-01
EN 998-1

Monolayer plaster mortar OC CSIII W2, for façade finishing and rain protection with finish scraping

Reaction to fire	Type A1
Water absorption	W2
Water permeability after climatic cycles conditioned	$\leq 1 \text{ ml/cm}^2$ after 48 hours
Diffusion coefficient of water vapour	$\mu \leq 15$
Adhesion after climatic cycles conditioned	$\geq 0,3 \text{ N/mm}^2$ Form A/B breakage