

DECLARATION OF PERFORMANCE

No.: 120131-156

1. **Product:**
PEGOLAND UNO BLANCO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA located at:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Normal-setting cementitious adhesive Pegoland Uno Blanco, for tile adhesion with medium to high absorption in interior and exterior floors and interior walls.
4. **Evaluation system:**
3
5. **Notified bodies:**
The following type tests were carried out: Nos. 2817368, 2815106, 2815107, 2815108, 2815118, 2815956 and 2822381, dated May, June, July and August 2008; Nos. 01-18/002356/1, 01-18/000695/1 and 01-18/028312/1, dated January and September 2018, at CEMOSA No. 1377 (Málaga); and Nos. 08/32308287, 08/32308289, 08/32309902, 08/32310165 and 08/32311199, dated May, July and October 2008, at APPLUS No. 0370 (Barcelona), obtaining the same product performance results for all manufacturing plants
6. **Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire:	E Class	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after thermal ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$	
Hazardous substances:	See safety data sheet	

The performance of the product identified in point 1 conforms with the declared performance in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on behalf of the manufacturer:

Place and date of issue: Málaga, 07/01/2025



Technical Director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 08	
PEGOLAND UNO BLANCO no. 120131-156 EN-12004:2007+A1:2012 Normal setting, cementitious adhesive for the installation of interior and exterior floors and interior walls.	
Reaction to fire:	E Class E
Adhesion: - Initial tensile adhesion strength:	$\geq 0,5 \text{ N/mm}^2$
Durability: - Tensile adhesion strength after water immersion: - Tensile adhesion strength after heat ageing: - Tensile adhesion strength after freeze-thaw cycles:	$\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$
Hazardous substances:	See safety data sheet