

DECLARATION OF PERFORMANCES

Nº: 230042

1. **Product:**
MORCEMDRY SF PLUS
2. **Manufacturer:**
GRUPO PUMA SL address:
C/ Conrado del Campo nº 2
29590 Campanillas (Málaga)
www.grupopuma.com
3. **Intended use:**
Coating mortar for superficial protection, flexible Bi-Component for concrete waterproofing, with minimum thickness coat of 2 mm
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonised technical specification
Permeability to CO ₂ :	Sd > 50 m	EN-1504-2:2004
Permeability to water steam:	Class 1	
Capillary absorption and water permeability:	$W \leq 0.1 \text{ kg/m}^2\text{h}^{0.5}$	
Thermal Compatibility:	It Accomplishes	
Adhesive strength by traction test:	$> 1.5 \text{ N/mm}^2$	
Dangerous Substances:	See safety data sheet	

Product performances identified in point 1 are in accordance to performances stated in point 5
 This declaration of features is issued under the sole responsibility of the manufacturer stated in point 2
 Signed by and on manufacturer behalf:
 Place and date of issue: Malaga, 01/07/2015



Technical Director: Jose A. Ferre Martínez

CE	
<p>GRUPO PUMA SL C/ Conrado del Campo nº - 29590 Campanillas (Málaga). 15 Nº: 230042</p>	
<p>IN-1504-2</p> <p>MORCEMDRY SF PLUS</p> <p>Coating Mortar for superficial protection, flexible Bi-component for concrete waterproofing, with minimum thickness coat of 2 mm</p>	
Permeability to CO₂:	Sd > 50
Permeability to water steam:	class 1
Thermal Compatibility:	it Accomplishes
Adhesive Strength by traction test:	>1.5 N/mm ²