

DECLARATION OF PERFORMANCES Nº: 230042

1.- Product:

MORCEMDRY SF PLUS

2.- Intended use:

Products for surface protection - coatings. Flexible two-component surface protection mortar for waterproofing concrete, with a minimum layer thickness of 2 mm. Principles 1-2 and 8. Methods 1.3; 2.2 and 8.2.

3.-Manufacturer:

GRUPO PUMA SL with registered address at: Avda Agrupación Córdoba nº 17 ,14014 Córdoba www.grupopuma.com

4.-System of evaluation and verification of the constancy of performance of products (EVCP) :

2+ plus 4

5.-Notified body:

Applus nº 0370, Certificate of conformity of production control nº0370-CPR-2578

6.- Declared performances:

Essential characteristics	Performances	Harmonised standards	Harmonised technical specifications
CO2 permeability	Sd>50m	EN 1062-6	EN-1504-2:2004
Water vapour permeability	Class 1	ISO 7783-1 ISO 7783-2	
Capillary absorption and water permeability	W≤0.1kg/m2h0.5	EN 1062-3	
Thermal compatibility	Comply	EN1062-11	
Adhesive strength by tensile test	>1.5N/mm2	EN 1542	
Hazardous substances	See Safety Data Sheet		

The performances of the product identified in point 1 comply with the performance declared in point 6. This declaration of features is issued under the sole responsibility of manufacturer stated in point 3, in accordance with Regulation (EU) No. 305/2011.

Signed by and on manufacturer behalf:

Place and date of issue: Córdoba, 08/08/2018.



Technical director: Jose A. Ferre Martínez



0370

GRUPO PUMA SL
Avda Agrupación Córdoba nº 17 ,14014 Córdoba
16
Nº: 230042

0370-CPR-2578

EN-1504-2

MORCEMDRY SF PLUS

Two-component flexible surface protection mortar for waterproofing concrete, with a minimum layer thickness of 2mm.

CO₂ permeability = $S_d \geq 50$

Water vapour permeability = Class 1

Capillary absorption and water permeability : $\leq 0.1 \text{ kg/m}^2 \text{ h}^{0.5}$

Thermal compatibility : Comply

Adhesive strength by tensile test: $\geq 1.5 \text{ N/mm}^2$