

DECLARATION OF PERFORMANCES

Nº: 801115-1

1. **Product:**
MORCEMSEC ENLUCIDO CON CAL
2. **Manufacturer:**
GRUPO PUMA SL com sede em::
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Coating mortar based on aerial lime for plastering and thick coat plastering. Thickness up to 2 cm.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonized technical specifications
Reaction to fire	Class A1	EN 998-1:2018
Water absorption	W2	
Water vapor diffusion coefficient	$\mu \leq 15$	
Thermal conductivity: ($\lambda_{10,dry}$)	PND	
Adhesion	$\geq 0.3 \text{ N/mm}^2$ Form of breakage A/B	
Durability	PND	
Hazardous substances	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2, in accordance with Regulation (EU) No. 305/2011.

Signed by and on manufacturer behalf:
Place and date of issue: Córdoba, 01/06/21



Technical director: Jose A. Ferre Martínez



GRUPO PUMA S.L
 Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
 14014 CÓRDOBA

20

MORCEMSEC ENLUCIDO CON CAL

Nº: 801115-1

EN 998-1

Coating mortar based on aerial lime for plastering and thick coat plastering. Thickness up to 2 cm.

Reaction to fire	Class A1
Water absorption	W2
Water vapor diffusion coefficient	$\mu \leq 15$
Adhesion	$\geq 0.3\text{N/mm}^2$ Form of breakage A/B