

DECLARATION OF BENEFITS

Nº: 215203

1.- Product: MORCEMFAST 40

2.- Intended use: thixotropic, medium-strength, fibre-reinforced, fast-setting, thixotropic mortar for concrete repair and plastering, for thicknesses between 4-40 mm.

3.-Manufacturer : GRUPO PUMA SPAIN residing at: Avda. Agrupación Córdoba 17 ,14014 Córdoba
www.grupopuma.com

4.-Evaluation system: 4

5.- Declared benefits

Key features	Services	Harmonised standards
Compressive strength	Classe R2	EN-1504-3:2005
Chloride ion content	≤0.05%	
Adhesion	≥0.8 Mpa	
Resistance to carbonation	Pass	
Thermal compatibility part 2	≥0.8Mpa	
Capillary absorption	≤0.5Kgm ⁻² h ^{-0.5}	
Hazardous substances	See Safety Data Sheet	
Reacción al fuego	A1	

The performance of the product identified in item 1 is in conformity with the performance declared in item 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in item 3. Signed by and on behalf of the manufacturer:



Place and date of issue: Cordoba, 24.08.23

Technical Director: Jose A. Ferre
Martínez



GRUPO PUMA SPAIN
Avda. Agrupación Córdoba 17 ,14014 Córdoba
23
Nº: 215203

EN 1504-3

MORCEMREST FAST 40

Medium-strength, thixotropic, fibre-reinforced, fast-setting, thixotropic mortar for concrete repair and plastering, for thicknesses between 4-40 mm, type CC

Compressive strength: Classe R2

Chloride ion content: $\leq 0.05\%$

Adhesion: $\geq 0.8\text{Mpa}$

Resistance to carbonation: Pass

Thermal compatibility Part 2: $\geq 0.8\text{Mpa}$

Capillary absorption: $\leq 0.5\text{Kg m}^{-2}\text{h}^{-0.5}$

Reaction to fire: A1