

DECLARATION OF PERFORMANCES

Nº: 120025-131

1.- Product: PEGOLAND ESPECIAL BLANCO

2.- Manufacturer: GRUPO PUMA SL with registered address at: C) Conrado del Campo nº 2 29590 Campanillas (Malaga). www.grupopuma.com

3.-Intended use: Normal setting cement based tile adhesive with reduced slip and extended open time, Pegoland Especial Blanco, for bonding ceramic tiles with water absorption > 3 % and vitreous glass tiles, on internal walls, internal and external floors and plasterboard drywalls.

4.- Evaluation system: 3

5.- Notified bodies: The following initial type tests have been conducted: nº71348, 71385, 71395, 71408, 71420, 71425, 71435, 71446, 71485, 74052, 75256, 75396, 75455, 75461, 75476 dated February, March and April 2004, in CEMOSA nº 1377 (Málaga) and nº 4019119 dated September 2004 and nº 31213997 dated November 2006 in APPLUS nº 0370 (Barcelona) with the same results obtained for all factories.

6.- Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adhesion: Initial tensile adhesion strength:	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Dangerous substances	See Safety Datasheet	

The performances of the product identified in point 1 comply with the performances declared in point 6.

This declaration of features is issued under the sole responsibility of the manufacturer stated in point 2

Signed for on behalf of the manufacturer by:

Date and place of issue: Malaga, 1/07/2015



Technical Director: Jose A. Ferre Martínez



0370, 1377

GRUPO PUMA SL
C) Conrado del Campo nº 2 29590 Campanillas (Málaga).
04

PEGOLAND ESPECIAL BLANCO

Nº: 120025-131

EN 12004: 2007+A1:2012

Normal setting cement based tile adhesive with reduced slip and extended open time, for internal walls, internal and external floors and plasterboard drywalls

Reaction to fire:	Class E
Adhesion: - Initial tensile adhesion	$\geq 0.5 \text{ N/mm}^2$
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 0.5 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$
Dangerous substances:	See Safety Datasheet

DECLARATION OF PERFORMANCES

Nº: 120032-158

1.- Product: PEGOLAND ESPECIAL GRIS

2.- Manufacturer: GRUPO PUMA SL with registered address at: C) Conrado del Campo nº 2 29590 Campanillas (Malaga). www.grupopuma.com

3.-Intended use: Normal setting cement based tile adhesive with reduced slip and extended open time, Pegoland Especial Blanco, for bonding ceramic tiles with water absorption > 3 % and vitreous glass tiles, on internal walls, internal and external floors and plasterboard drywalls.

4.- Evaluation system: 3

5.-Notified bodies: The following initial type tests. have been conducted: 71383, 71416, 71426, 71447, 75449, 79618, 80108 dated March, April, June and September 2004, and nº 201/1/2012/252 dated January 2012 in CEMOSA nº 1377 (Málaga) and nº 5029472, 5026638 dated July and September 2005 in APPLUS nº 0370 (Barcelona) with the same results obtained for all factories.

6.- Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adhesion:		
- Initial tensile adhesion strength:	$\geq 0.5\text{N/mm}^2$	
Durability:		
- Tensile adhesion after water immersion:	$\geq 0.5\text{N/mm}^2$	
- Tensile adhesion after heat aging:	$\geq 0.5\text{N/mm}^2$	
- Tensile adhesion after freeze/thaw cycles:	$\geq 0.5\text{N/mm}^2$	
Dangerous substances	See Safety Datasheet	

The performances of the product identified in point 1 comply with the performances declared in point 6.

This declaration of features is issued under the sole responsibility of the manufacturer stated in point 2

Signed for on behalf of the manufacturer by:

Date and place of issue: Malaga, 1/07/2015



Technical Director: Jose A. Ferre Martínez



0370, 1377

GRUPO PUMA SL
C) Conrado del Campo nº 2 29590 Campanillas (Málaga).
04

PEGOLAND ESPECIAL GRIS

Nº: 120032-158

EN 12004: 2007+A1:2012

Normal setting cement based tile adhesive with reduced slip and extended open time, for internal walls, internal and external floors and plasterboard drywalls.

Reaction to fire:	Class E
Adhesion: - Initial tensile adhesion	$\geq 0.5 \text{ N/mm}^2$
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 0.5 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$
Dangerous substances	See Safety Datasheet