

## DECLARATION OF PERFORMANCE

### Nº: 501866

1. **Product:**  
PAVILAND INDUSTRIAL 15R AUTOLEVELANTE
2. **Manufacturer:**  
GRUPO PUMA ESPAÑA S.L located in: C/  
Avda. Agrupación Córdoba, 17  
14014 CÓRDOBA  
[www.grupopuma.com](http://www.grupopuma.com)
3. **Intended use:**  
Rapid-hardening fibre-reinforced self-levelling floor screed, type CT-C40-F5-A12-B2, for industrial interior use in thicknesses from 5 to 15 mm.
4. **Evaluation system:**  
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type E	EN 13813:2014
Emission of harmful substances	CT	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	C40	
Flexural strength	F5	
Wear resistance	A12	
Bond strength	B2	
Sound insulation	NPD	
Acoustic absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Hazardous substances	Consult safety data sheet	

The performance of the product identified in point 1 conforms with the declared performance in point 5.

This Declaration of Performance is issued under the sole responsibility of the manufacturer indicated in point 2 in accordance with Regulation (EU) No 305/2011.

Signed by and on manufacturer behalf:  
Place and Date of issue: Córdoba, 10/02/26



Technical Director: Jose A. Ferre Martínez  
Página 1 de 2



GRUPO PUMA ESPAÑA S.L  
 Avda. Agrupación Córdoba, 17  
 14014 CÓRDOBA

26

**PAVILAND INDUSTRIAL 15R AUTOLEVELANTE**

**Nº: 501866**

**EN 13813**

Fast setting fibre-reinforced self-levelling floor screed, type CT-C40-F5-A12-B2, for industrial interior use in thicknesses from 5 to 15 mm.

<b>Reaction to fire</b>	Type E
<b>Emission of harmful substances</b>	CT
<b>Compressive strength</b>	C40
<b>Flexural strength</b>	F5
<b>Wear resistance</b>	A12
<b>Bond strength</b>	B2
<b>Hazardous substances</b>	Consult safety data sheet