

## DECLARATION DE PERFORMANCES Nº: 210108

**1.- Product:**

MORCEMDRY F

**2.- Expected use:**

Surface protection products - coating. Two-component flexible coating for superficial waterproofing concrete with a minimum layer thickness of 2 mm. Principles 1-2 and 8. Methods 1.3: 2.2 and 8.2

**3.-Manufacturer:**

GRUPO PUMA ESPAÑA located at: Avda Agrupación Córdoba No. 17, 14014 Córdoba www.grupopuma.com

**4.-System for assessment and verification of the constancy of product performance (AVCP)**

2+ and 4

**5.-Notified body:**

Applus No. 0370 Certificates of conformity for Production Control No. 0370-CPR-2578 and No. 0370-CPR-4693. **6.-**

**Declared performances**

Essential characteristics	Performances	Harmonized norms	Harmonized Technical Specification
CO <sub>2</sub> permeability	Sd>50m	EN 1062-6	EN-1504-2: 2004
Permeability to water vapour	Type 1	ISO 7783-1 ISO 7783-2	
Capillary absorption and permeability to water	W≤0.1kg/m <sup>2</sup> h <sup>0.5</sup>	EN 1062-3	
Thermal compatibility	Pass	EN1062-11	
Crack-bridging ability	Type 5	EN1062-7	
Adhesive strength by pull-off test	> 1,5 N/mm <sup>2</sup>	EN 1542	
Adhesion on wet concrete	> 1,5 N/mm <sup>2</sup>	EN 13578	
Hazardous substances	See safety data sheet		

The performances of the product identified in point 1 comply with the performance declared in point 6.

This declaration of features is issued under the sole responsibility of manufacturer stated in point 3, in accordance with Regulation (EU) No. 2024/3110.

Signed by and on manufacturer behalf

Place and date of issue: Córdoba, 01/01/2025



Technical director: José A. Ferre Martínez



0370

**GRUPO PUMA ESPAÑA**  
**Avda. Agrupación Córdoba 17**  
**14014 Córdoba**  
**16**  
**Nº: 210108**

**0370-CPR-2578**  
**0370-CPR-4693**

**EN 1504-2**

**MORCEMDRY F**

Two-component flexible coating for superficial waterproofing  
 concrete, with a minimum layer thickness of 2mm.

<b>CO<sub>2</sub> permeability</b>	Sd>50m
<b>Permeability to water vapour</b>	Type 1
<b>Capillary absorption and permeability to water</b>	≤0.1kg/m <sup>2</sup> h <sup>0.5</sup>
<b>Thermal compatibility</b>	Pass
<b>Crack-bridging ability</b>	Type 5
<b>Adhesive strength by pull-off test</b>	>1.5 N/mm <sup>2</sup>
<b>Adhesion on wet concrete</b>	>1.5 N/mm <sup>2</sup>