

DECLARATION OF PERFORMANCES

Nº: 120001-127

1.- Product: PEGOLAND PLUS BLANCO

2. - Manufacturer: GRUPO PUMA SL with registered address at: C) Conrado del Campo nº 2 29590 Campanillas (Malaga). www.grupopuma.com

3.-Intended use: Cement based normal setting tile adhesive with reduce slip, Pegoland Plus Blanco, for bonding ceramic tiles with water absorption >3 % for internal walls, internal and external floorings and baseboards.

4.- Evaluation system: 3

5. - Notified bodies: The following initial type tests. have been conducted: nº 71349, 71385, 71409, 71432, 71435, 74048, 74640, 75181, 75255, 75453, 75458, 75472, 76378 dated February, March and April de 2004, nº 201/1/2011/1049 dated May 2011 in CEMOSA nº 1377 (Malaga), and nº 4019118, 4025971 dated September 2004 in APPLUS nº 0370 (Barcelona) with the same results obtained in all factories.

6.- Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength:	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Dangerous substances:	See Safety Datasheet	

The performances of the product identified in point 1 comply with the performances declared in point 6.

This declaration of features is issued under the sole responsibility of the manufacturer stated in point 2

Signed for on behalf of the manufacturer by:

Date and place of issue: Malaga, 1/07/2015



Technical Director: Jose A. Ferre Martínez



0370, 1377

GRUPO PUMA SL
C) Conrado del Campo nº 2 29590 Campanillas (Málaga).
04

PEGOLAND PLUS BLANCO

Nº: 120001-127

EN 12004: 2007+A1:2012

Cement based normal setting tile adhesive with reduce slip for internal walls, internal and external floorings and baseboards.

Reaction to fire:

Class E

Adhesion:

- Initial tensile adhesion

$\geq 0.5 \text{ N/mm}^2$

Durability:

- Tensile adhesion after water immersion:

$\geq 0.5 \text{ N/mm}^2$

- Tensile adhesion after heat aging:

$\geq 0.5 \text{ N/mm}^2$

- Tensile adhesion after freeze/thaw cycles:

$\geq 0.5 \text{ N/mm}^2$

Dangerous substances

See Safety Datasheet

DECLARATION OF PERFORMANCES

Nº: 120018-157

1.- Product: PEGOLAND PLUS GRIS

2. - Manufacturer: GRUPO PUMA SL with registered address at: C) Conrado del Campo nº 2 29590 Campanillas (Malaga). www.grupopuma.com

3.-Intended use: Cement based normal setting tile adhesive with reduced slip, Pegoland Plus Gris, for bonding ceramic tiles with water absorption >3 % for internal walls, internal and external floorings and baseboards.

4.- Evaluation system: 3

5. - Notified bodies: The following initial type tests. have been conducted: nº 71383, 71410,71436, 71448, 73591,75254, 75454, 75469, 80106 dated February, March, April, May and June 2004, , nº 2703403 dated March 2007 in CEMOSA nº 1377 (Malaga), and nº 4019120 dated November 2004, nº 5029471 dated July 2005, nº 31212761 dated August 2006 in APPLUS nº 0370 (Barcelona) with the same results obtained in all factories.

6.- Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength:	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Dangerous substances:	See Safety Datasheet	

The performances of the product identified in point 1 comply with the performances declared in point 6.

This declaration of features is issued under the sole responsibility of the manufacturer stated in point 2

Signed for on behalf of the manufacturer by:

Date and place of issue: Malaga, 1/07/2015



Technical Director: Jose A. Ferre Martínez



0370, 1377

GRUPO PUMA SL

C) Conrado del Campo nº 2 29590 Campanillas (Málaga).
04

PEGOLAND PLUS GRIS

Nº: 120018-157

EN 12004: 2007+A1:2012

Cement based tile adhesive of normal setting with reduce slip for internal walls, internal and external floorings and baseboards.

Reaction to fire:

Class E

Adhesion:

- Initial tensile adhesion

$\geq 0.5 \text{ N/mm}^2$

Durability:

- Tensile adhesion after water immersion:

$\geq 0.5 \text{ N/mm}^2$

- Tensile adhesion after heat aging:

$\geq 0.5 \text{ N/mm}^2$

- Tensile adhesion after freeze/thaw cycles:

$\geq 0.5 \text{ N/mm}^2$

Dangerous substances

See Safety Datasheet