

DECLARATION OF PERFORMANCE

No.: 105309

- 1. Product:**
PEGOLAND PROFESIONAL MAX S1 BLANCO
- 2. Manufacturer:**
GRUPO GRUPO PUMA ESPAÑA located at:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
- 3. Intended use:**
Improved deformable cementitious adhesive with reduced slip and extended open time, Pegoland Profesional Max S1 Blanco, for the installation of interior and exterior floors, interior and exterior walls, façades, radiant heating floors systems, cold rooms, large area floors and overlays, pools rendering and installation over cementitious waterproofing, adhesion of all type of ceramic pieces, porcelain stoneware, marble, granite and natural stone.
- 4. Evaluation system:**
3
- 5. Notified bodies:**
They have conducted the tests labelled as No. 001-24/001991/1, 001-24/001992/1, and 001-24/001993/1, dated January 2024 at CEMOSA No. 1377 (Málaga), obtaining the same results for the product from all factories.
- 6. Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adhesion: - Initial adhesion to traction	≥ 1,0 N/mm ²	
Durability: - Adhesion to traction after water immersion - Adhesion to traction after thermal ageing - Adhesion to traction after ice / thaw cycles	≥ 1,0 N/mm ² ≥ 1,0 N/mm ² ≥ 1,0 N/mm ²	
Hazardous substances:	Consult safety data sheet	

The performance of the product identified in point 1 conforms with the declared performance in point 6.
This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer indicated in point 2.

Signed by and on behalf of the manufacturer:
Place and Date of issue: Málaga, 08/02/2024



Technical Director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 24	
PEGOLAND PROFESIONAL MAX S1 BLANCO Nº: 105309 EN-12004:2007+A1:2012 Improved deformable cementitious adhesive with reduced slip and extended open time, for the installation of interior and exterior floors, interior and exterior rendering, façades, radiant heating floors systems, cold rooms, large area floors and overlays, pool rendering, and installation over cementitious waterproofing systems.	
Reaction to fire:	Class E
Adherence:	
- Initial adhesion to traction:	≥ 1,0 N/mm ²
Durability:	
- Adhesion to traction after water immersion:	≥ 1,0 N/mm ²
- Adhesion to traction after thermal ageing:	≥ 1,0 N/mm ²
- Adhesion to traction after ice / thaw cycles:	≥ 1,0 N/mm ²
Hazardous substances:	Consult safety data sheet