

DECLARATION OF PERFORMANCES

Nº: 600770-01

1.- Product: MORCEMDUR R

2.- Intended use: Waterproofing one-coat render, type OC-CSIII-W2, for protection and decoration of facades with scraped finish.

3. - Manufacturer: GRUPO PUMA SL with registered address at: C) Conrado del Campo nº 2 29590 Campanillas (Malaga). www.grupopuma.com

4.- Evaluation systems: 4

5.- Declared characteristics:

Essential characteristics	Features	Harmonised technical features
Reaction to fire:	Class A1	EN-998-1:2010
Capillary water absorption:	W2	
Permeability to water after climatic conditioning cycles:	≤ 1 ml/cm ² after 48 hours	
Water vapour permeability coefficient:	μ ≤15	
-Thermal conductivity: (λ _{10,seco})	NPD	
Adhesion:	≥0.3 N/mm ² Fracture pattern A/B	
Durability:	Evaluation based on the valid norms in the place of use	
Dangerous substances	See Safety Datasheet	

The product features identified in point 1 comply with the features declared in point 5.

This declaration of features is issued under the sole responsibility of the manufacturer stated in point 3.

Signed by and on behalf of the manufacturer:

Date and place of issue: Malaga 1/07/2015



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA SL
C) Conrado del Campo nº 2 29590 Campanillas (Málaga).
05
Nº: Nº: 600770-01

EN 998-1

MORCEMDUR R

Waterproofing one-coat render, type OC-CSIII-W2, for protection and decoration of facades with scraped finish.

Reaction to fire: Class A1

Capillary water absorption: W2

Permeability to water after climatic conditioning cycles: ≤ 1 ml/cm² after 48 hours

Water vapour permeability coefficient: $\mu \leq 15$

Adhesion: ≥ 0.3 N/mm² Fracture pattern A/B

Thermal conductivity NPD

Durability: Evaluation based on the valid norms in the place of use