

DECLARATION DE PERFORMANCES Nº: 220022

1. **Product:**
MORCEMGROUT 500 PLUS
2. **Intended use:** Mortar of very high resistances, for fillings and anchors of machinery, leveling of supports and bridges, application thickness from 20 to 200 mm. Principle 4, method 4.1 according to 1504-6 and 4.2 according to 1504-9.
3. **Manufacturer:**
GRUPO PUMA SL, located in:
Avda Agrupación Córdoba 17,
14014 Córdoba
www.grupopuma.com
4. **Evaluation system:**
2+4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Resistance to starting, displacement	≤0.6mm at 75KN load	EN-1504-6:2006
Chloride ion content	≤0.05%	
Hazardous substances	See safety datasheet	
Reaction to fire	A1	

The performances of the product identified in point 1 comply with the performance declared in point 5.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 3.
Signed by and on manufacturer behalf
Place and date of issue: Córdoba, 28.06.22



Technical director: José A. Ferre Martínez



GRUPO PUMA S.L
Avda. Agrupación Córdoba 17
14014 Córdoba

22
Nº: 220022

**MORCEMGROUT 500 PLUS
1504-6**

Mortar of very high resistances, for fillings and anchors of machinery, leveling of supports and bridges, application thickness from 20 to 200 mm.

Resistance to starting, displacement ≤0.6mm at 75KN load

Chloride ion content ≤0.05%

Reaction to fire A1