

DECLARATION OF PERFORMANCES

Nº: 210022

1.- Product:
MORCEM RAPIDO

2.-Intended use:
Type CC mortar for non-structural concrete repair, for small concrete repairs, anchoring of door and window frames, where a fast setting and hardening mortar is required.

3.-Manufacturer:
GRUPO PUMA SL located in: C) Conrado del Campo nº 2 29590 Campanillas (Málaga) www.grupopuma.com

4.-Evaluation system: 4

5.-Declared performances:

Essential characteristics	Performances	Harmonised standards
Compressive strength	Class R1	EN-1504-3:2005
Chloride ion content	≤0.05%	
Adhesion	≥0,8Mpa	
Thermal compatibility Part 4	Without cracks	
Capillary absorption	≤0.5Kgm ⁻² h ^{-0.5}	
Hazardous substances	See safety data sheet	
Reaction to fire	A1	

The performance of the product identified in point 1 is in accordance with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 3.

Signed by and on behalf of the manufacturer:
Place and Date of issue: Malaga, 01/07/2015

Technical director: Jose A. Ferre Martínez





GRUPO PUMA SL
C) Conrado del Campo nº 2 29590 Campanillas (Málaga)
13
Nº: 210022

EN 1504-3

MORCEM RAPIDO

Mortar type CC for non-structural concrete repair, for small concrete repairs, anchoring of door and window frames, where a fast setting and hardening mortar (hydraulic cement based) is required.

Compressive strength: Class R1

Chloride ion content: $\leq 0.05\%$

Adhesion: $\geq 2\text{Mpa}$

Thermal compatibility Part 1: Without crack

Capillary absorption : $\leq 0.5\text{Kg m}^{-2}\text{h}^{-0.5}$

Reaction to fire : A1